

EVR-GARD COATINGS COMPANY -- 4900 TRAFFIC PAINT -- 8010-00F056648
===== Product Identification =====

Product ID:4900 TRAFFIC PAINT
MSDS Date:03/12/1997
FSC:8010
NIIN:00F056648
MSDS Number: CHNJH
==== Responsible Party ====
Company Name:EVR-GARD COATINGS COMPANY
Address:16400 GARFIELD AVENUE
City:PARAMOUNT
State:CA
ZIP:90723-5000
Country:US
Info Phone Num:213-531-0131
Emergency Phone Num:213-531-0131
CAGE:5G582
==== Contractor Identification ====
Company Name:EVR-GARD COATINGS CO
Address:16400 GARFIELD AVE
Box:City:PARAMOUNT
State:CA
ZIP:90723
Country:US
Phone:310-531-0131
CAGE:5G582

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN/EYES: PRIMARY IRRITANT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, REDNESS, RASH, NAUSEA, HEADACHE,
DIZZINESS
Medical Cond Aggravated by Exposure:DERMATITIS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/CLEAN WATER
FOR 10 MINS. SKIN: WASH W/SOAPY WATER THOROUGHLY. INGESTION: INDUCE
VOMITING W/1 OZ OF SYRUP OF IPECAC FOLLOWED IN 5 MINS W/A GLASS OF
WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Lower Limits:0.6

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:THIS IS A WATER-BASED PRODUCT. WILL NOT SUPPORT COMBUSTION.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/ANY ABSORBENT MATERIAL, SAWDUST, SAND, CLAY & FLUSH AREA W/LOTS OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING. DON'T TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED MASKS DURING APPLICATION TO AVOID EXCESSIVE INHALATION OF VAPORS. OPEN WINDOWS & DOORS/USE OTHER MEANS TO INSURE FRESH AIR ENTRY DURING APPLICATION/DRYING.

Ventilation:ADEQUATE AT ALL TIMES DURING HANDLING & APPLICATION. INSURE ADEQUATE SUPPLY OF FRESH AIR AT ALL TIMES.

Protective Gloves:BUNA NTRILE

Eye Protection:CHEMICAL GOGGLES, MASKS

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. OBSERVE STANDARD HYGIENIC PRACTICES WHEN HANDLING THIS PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:>1

Spec Gravity:1.3

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:DILUTABLE

Appearance and Odor:WHITE PAINT & COLORS W/SLIGHT AMMONIA SMELL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, ALKALIS, MATERIALS THAT REACT W/WATER.

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods: PLACE ALL HAZARDOUS WASTES W/ ABSORBENTS USED IN 55-GAL METAL DRUMS & DISPOSE OF IN APPROVED DUMPSITE IN ACCORDANCE W/ LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.