______ Section 1 -- PRODUCT AND COMPANY IDENTIFICATION PRODUCT NUMBER HMIS CODES Health 2 Flammability 4 Reactivity 0 20000 PRODUCT NAME TRI-FLOW* Superior Lubricant With Teflon* (Aerosol) MANUFACTURER'S NAME EMERGENCY TELEPHONE NO. THE SHERWIN-WILLIAMS COMPANY (216) 566-2917 Consumer Group - Industrial Cleveland, OH 44115 DATE OF PREPARATION INFORMATION TELEPHONE NO. (216) 566-2902 18-NOV-05 ______ Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS by WT CAS No. INGREDIENT UNITS VAPOR PRESSURE 10 74-98-6 Propane ACGIH TLV 2500 ppm 760 mm OSHA PEL 1000 ppm 10 106-97-8 Butane ACGIH TLV 800 ppm OSHA PEL 800 ppm 760 mm 24 64742-47-8 Heavy Aliphatic Solvent ACGIH TLV Not Available OSHA PEL Not Available 0.01 mm 41 64742-52-5 Heavy Naphthenic Petroleum Oil ACGIH TLV 5 mg/m3 as Mist OSHA PEL 5 mg/m3 as Mist 64741-97-5 Naphthenic Oil 2 ACGIH TLV 5 mg/m3 as Mist OSHA PEL Not Available 3 64742-65-0 Heavy Paraffinic Oil ACGIH TLV 5 mg/m3 as Mist OSHA PEL 5 mg/m3 as Mist thoxymethylethoxypropanol
ACGIH TLV 100 ppm (Skin)
ACGIH TLV 150 ppm (Skin) STEL
OSHA PEL 100 ppm (Skin)
OSHA PEL 150 ppm (Skin) STEL 2 34590-94-8 2-Methoxymethylethoxypropanol 0.4 mm 2 628-63-7 Amyl Acetate ACCIH TLV 100 ppm OSHA PEL 100 ppm 4 mm ______

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

Continued on page 2

20000

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

INGESTION: Do not induce vomiting.

Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT LEL UEL Propellant < 0 F 0.6 14.0

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

internally. Keep out of the reach of children.

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields. OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT 6.50 lb/gal 778 g/l
SPECIFIC GRAVITY 0.78
BOILING POINT <0 - 500 F <-18 - 260 C
MELTING POINT Not Available
VOLATILE VOLUME 56 2

VOLATILE VOLUME 56 %
EVAPORATION RATE Faster than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER N.A.

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

Volatile Weight 48.20 % Less Water and Federally Exempt Solvents

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA CAS No.	Ingredient Name	_
74-98-6	Propane	_
	LC50 RAT 4HR Not Available	
	LD50 RAT Not Available	
106-97-8	Butane	
	LC50 RAT 4HR Not Available	
	LD50 RAT Not Available	
64742-47-8	Heavy Aliphatic Solvent	
	LC50 RAT 4HR Not Available	
	LD50 RAT Not Available	
64742-52-5	Heavy Naphthenic Petroleum Oil	
	LC50 RAT 4HR Not Available	
	LD50 RAT Not Available	
64741-97-5	Naphthenic Oil	
	LC50 RAT 4HR Not Available	
	LD50 RAT Not Available	
64742-65-0	Heavy Paraffinic Oil	
	LC50 RAT 4HR Not Available	
*** *. *	LD50 RAT Not Available	
34590-94-8	2-Methoxymethylethoxypropanol	
	LC50 RAT 4HR Not Available	
COO CO 7	LD50 RAT 5135 mg/kg	
628-63-7	Amyl Acetate	

Section 12 -- ECOLOGICAL INFORMATION

LC50 RAT 4HR Not Available LD50 RAT 6500 mg/kg

6500 mg/kg

ECOTOXICOLOGICAL INFORMATION

No data available.

Continued on page 5

______ Section 13 -- DISPOSAL CONSIDERATIONS WASTE DISPOSAL METHOD Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution. ______ Section 14 -- TRANSPORT INFORMATION No data available. ______ Section 15 -- REGULATORY INFORMATION ______ SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION CAS No. CHEMICAL/COMPOUND % by WT % Element CAS NO. CREMICAL/COMPOUND 8 DY WI 8 EL 2 0.05 Barium Compound CALIFORNIA PROPOSITION 65 WARNING: This product contains a chemical known to the State of California to cause cancer. TSCA CERTIFICATION All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory. ______ Section 16 -- OTHER INFORMATION ______ This product has been classified in accordance with the hazard criteria of the Canadian Controlled Froducts Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.