

MATERIAL SAFETY DATA SHEET

(CONFORMS TO THE REQUIREMENTS OF)
29CFR 1910.1200

BUTANE

DATE OF PREPARATION: **JULY 27, 1994**

SECTION I

MANUFACTURER'S NAME: COOPER HAND TOOLS/TURNER
STREET ADDRESS: 821 PARK AVENUE
SYCAMORE, ILLINOIS 60178
EMERGENCY RESPONSE TELEPHONE NO. (CHEM TREC): 800-424-9300
TELEPHONE NUMBER FOR INFORMATION: (815) 895-4545

SECTION II - IDENTITY

MANUFACTURER'S IDENTIFICATION NUMBERS: WB1

IDENTITY (As Used On Label and List): Butane-Liquefied Petroleum Gas

SYNONYMS: LP Gas, Isobutane, A-31

CHEMICAL NAME: BUTANE

CHEMICAL FAMILY: HYDROCARBON, LP GAS

CHEMICAL FORMULA: C₄H₁₀

D.O.T. HAZARD CLASS: FLAMMABLE GAS

D.O.T. IDENTIFICATION NUMBER: Liquefied Petroleum Gas UN1075
or Butane UN1011

IATA IDENTIFICATION NUMBER: UN1011

DEGREE OF HAZARD	
HEALTH	1
FIRE	4
REACTIVITY	0

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS #	OSHA PEL	PEL/TLV SOURCE	Other Limits Recommended	% (percent)
ISOBUTANE	68476-86-8	NE	800PPM, ACGIH		100%

SECTION IV - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 11°F - (12°C)
SPECIFIC GRAVITY (H₂O = 1): 0.56
PRESSURE IN CAN AT 70°F: APPROXIMATELY 31 PSIG
PERCENT VOLATILE BY WEIGHT: 100%
VAPOR DENSITY (AIR = 1): 2.0
EVAPORATION RATE (BUACE = 1): FLASH EVAPORATES
SOLUBILITY IN WATER: NEGLIGIBLE
APPEARANCE AND ODOR: LIQUIFIED COMPRESSED GAS, FLASH EVAPORATES AT ROOM TEMPERATURE WHEN RELEASED FROM CAN, COLORLESS GAS WITH STRONG MERCAPTAN (SKUNK-LIKE) ODOR DUE TO STENCHING AGENT ADDED TO GAS FOR LEAK DETECTION PURPOSES.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -LESS THAN -100°F (-79°C) ESTIMATED
FLAMMABLE LIMITS: % BY VOLUME IN AIR LEL: [1.8] UEL: [8.4]
EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM OR CARBON DIOXIDE (CO₂)
SPECIAL FIRE FIGHTING PROCEDURES: AVOID POSSIBLE ACCUMULATIONS OF VAPORS AT FLOOR LEVEL AS VAPOR IS HEAVIER THAN AIR. SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS. THIS PRODUCT IS EXTREMELY FLAMMABLE AT ALL TIMES. KEEP AWAY FROM ANY SOURCES OF INADVERTANT IGNITION, INCLUDING HEAT, FIRE, SPARKS, OR FLAME.
UNUSUAL FIRE AND EXPLOSION HAZARDS: AVOID POSSIBLE BURSTING OF AEROSOL CAN. DO NOT STOP WHERE TEMPERATURE MAY EXCEED 120°F. DO NOT PUNCTURE OR INCINERATE.

SECTION VI - REACTIVITY DATA

STABILITY: Unstable [] Conditions to avoid: HEAT, SPARKS, FLAMES, STRONG OXIDIZERS
Stable [XX]
INCOMPATIBILITY (Material to Avoid): CHLORINE AND OTHER STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: CARBON MONOXIDE, OTHER CARBON OXIDES
HAZARDOUS POLYMERIZATION: May Occur []
Will Not Occur [XX]

SECTION VII - HEALTH AND HAZARD DATA

SUGGESTED EXPOSURE GUIDELINE 800 PPM**PRIMARY ROUTE OF EXPOSURE:****INHALATION, SKIN CONTACT****INHALATION: DIZZINESS, DISORIENTATION, HEADACHE, ANESTHESIA.****SKIN CONTACT: VAPORS ARE NOT IRRITATING. FREEZE BURNS OR FROSTBITE POSSIBLE IF SKIN IS IN PROLONGED CONTACT WITH VAPORIZING LIQUID.****EYE CONTACT: SAME AS SKIN CONTACT.****CARCINOGENICITY: NONE OF THE COMPONENTS IN THIS MATERIAL ARE LISTED BY IARC, NTP, OSHA, OR ACGIH AS A CARCINOGEN.****EMERGENCY AND FIRST AID PROCEDURES:****INHALATION:****Remove to fresh air. If breathing ceases, administer artificial respiration followed by oxygen. Seek medical attention.****SKIN CONTACT:****Wash with soap and water. Remove soaked clothing to avoid prolonged skin contact.****EYE CONTACT:****Immediately flush eyes with running water for at least 15 minutes. If irritation develops, seek medical attention.****INGESTION:****NA, product is gaseous at normal temperature and pressure.****SUBCHRONIC & CHRONIC EFFECTS OF OVEREXPOSURE:****Ames test exhibited negative results. Human volunteers exposed repeatedly to hydrocarbon mixture gases at concentrations ranging from 250 to 1000 ppm exhibited no cardiac or pulmonary function abnormalities.**

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

PROTECT FROM ANY IGNITION SOURCE, KEEP AWAY FROM HEAT, FIRE, SPARKS, OR FLAME. VENTILATE AREA WELL. AVOID ACCUMULATION OF VAPOR AT LOW LEVELS.

WASTE DISPOSAL METHOD:

DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE OR INCINERATE.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

DO NOT STORE WHERE TEMPERATURE MAY EXCEED 120°F. STORE AWAY FROM FIRE, SPARKS, OR FLAME. STORE IN SUITABLE AREA FOR HAZARDOUS MATERIALS STORAGE.

D.O.T. SHIPPING CLASSIFICATION: LIQUIFIED PETROLEUM GAS, 2.1

HAZARD CLASS: FLAMMABLE GAS

ID NUMBER: UN1075

LABEL REQUIRED: FLAMMABLE GAS

SPECIAL PRECAUTIONS:**PRECAUTIONS FOR USAGE**

DO NOT USE NEAR HEAT, FIRE, FLAME, OR SPARKS. AVOID EXCESSIVE BREATHING OF VAPOR. DO NOT SPRAY IN DIRECTION OF BODY. USE ONLY IN ACCORDANCE WITH DIRECTIONS.

SECTION IX

RESPIRATION PROTECTION: IF TLV IS EXCEEDED WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING DEVICE OR RESPIRATOR.

VENTILATION: MUST BE ADEQUATE TO MAINTAIN VAPORS AT LESS THAN 800 PPM, PARTICULARLY FLOOR LEVEL AS VAPORS ARE HEAVIER THAN AIR

PROTECTIVE GLOVES: NONE NEEDED FOR NORMAL USE. SOLVENT-RESISTANT RUBBER TYPE RECOMMENDED IF PROLONGED EXPOSURE EXPECTED.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES RECOMMENDED.

NOTICE

TURNER/DIVISION OF COOPER HAND TOOLS, EXPRESSLY DISCLAIMS ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OF INFORMATION PROVIDED HEREIN.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE MANUFACTURER AND/OR RECOGNIZED SOURCES. WHILE THE INFORMATION IS BELIEVED TO BE ACCURATE, TURNER MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR SUFFICIENCY. CONDITIONS OF USE ARE BEYOND TURNER'S CONTROL AND THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM THE PUBLICATION OR USE OF, OR RELIANCE UPON, INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER PROCESS.

