

Carmeuse Lime & Stone 11 Stanwix Street, 11<sup>th</sup> Floor Pittsburgh, PA 15222 Phone: 412-995-5500 Fax: 412-995-5594

Date of Origin:	06/05/02
Date of Review:	06/12/2008
Revision No.	8

# Material Safety Data Sheet

Product Name:

# **HIGH CALCIUM LIMESTONE**

### INFOTRAC: 800-535-5053 [In case of an emergency call this number 24 HOURS a day 7 DAYS a week.]

#### 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

#### **1.1. Identification of the substance:**

Chemical name:	Calcium carbonate
Product name & synonyms:	Agricultural Stone-Small, Agricultural Stone-Large, Sinter Stone, #8's Limestone, #1 Grit Pulverized Limestone, #3 Grit Pulverized Limestone, Grades B, F, G Pulverized Limestone, ROM Stone, ROMF, Calcite, Ground Limestone, grades GPS-20, GPS-325
Formula:	CaCO <sub>3</sub>
CAS #:	471-34-1
Molecular Weight:	100.09
Material Uses:	Manufacture of lime and lime related products, and aggregate

#### 1.2. Company:

Main Office: 11 Stanwix Street, 11 <sup>th</sup> Floor Pittsburgh, PA 15222	Telephone: Fax:	412-995-5500 412-995-5594
Canadian Office: P.O. Box 190 Ingersoll, Ontario N5C 3K5	Telephone: Fax:	519-423-6283 519-423-6545

2. COMPOSITION / INFORMATION ON INGREDIENTS			
Ingredient	% by Weight	CAS#	Exposure Limits
Calcium carbonate	> 90	471-34-1	OSHA PEL: 15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (respirable) ACGIH TLV: 10 mg/m <sup>3</sup> O. Reg. 833 TWAEV: 10 mg/m <sup>3</sup>
Magnesium carbonate	< 5	546-93-0	OSHA PEL: 15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (respirable) ACGIH TLV: 10 mg/m <sup>3</sup> O. Reg. 833 TWAEV: 10 mg/m <sup>3</sup>
Silica - crystalline quartz	0.1 - 1	14808-60-7	OSHA PEL: 30 mg/m <sup>3</sup> / (% silica + 2) (total) 10 mg/m <sup>3</sup> / (% silica + 2) (respirable) ACGIH TLV: 0.025 mg/m <sup>3</sup> (respirable) O. Reg. 845 TWAEV: 0.1 mg/m <sup>3</sup>

#### 3. HAZARDS IDENTIFICATION AND CLASSIFICATION

- **Overview:** High calcium limestone is an odorless white or grayish-white granular powder. Contact can cause irritation to eyes, skin, respiratory system, and gastrointestinal tract. Contact may irritate eyes, skin, gastrointestinal tract, and respiratory system.
- **Eyes:** May cause irritation of the eyes.
- Skin: May cause dryness and irritation of the skin.
- **Ingestion:** May cause discomfort or constipation if swallowed. If large quantities are swallowed, it may cause nausea, hypercalcaemia or hemorrhage.
- Inhalation: May cause irritation of the respiratory system resulting in coughing and/or sneezing. Higher exposures may cause a build up of fluid in the longs with severe shortness of breath. This product is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product may contain trace amounts of crystalline quartz silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled. Inhalation of silica can also cause a chronic lung disorder, silicosis.
- Irritant: Eyes, mucous membranes, skin, respiratory tract.
- Flammability: This product is not flammable or combustible
- **Explosive**: This product is not explosive
- **Reactivity:** May react violently with strong acids producing heat and possible steam explosion in confined space.
- 4. HEALTH EFFECTS AND TREATMENTS

#### Health Effects:

Inhalation:	Acute: irritation, cough, sneezing. Chronic: persistent coughing and breathing problems.		
	Long-term exposure to silica can cause a chronic lung disorder, silicosis.		
Eyes:	Acute: May cause irritation Chronic: no known effects.		
Skin:	Acute: May cause dryness and irritation. Chronic: no known effects.		
Ingestion:	Acute: Gastro-intestinal irritation. Large quantities may cause discomfort and constipation		
	Chronic: no known effects.		
Treatments:			
Inhalation:	Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration.		
Eyes:	Immediately flush eyes with large amounts of water for at least 15 minutes. Pull back the eyelid to make sure all the limestone dust has been washed out. If irritation persists, seek medical attention. Do not rub eyes.		
Skin:	Flush exposed area with large amounts of water.		
Ingestion:	Give large quantities of water or fruit juice. Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.		

5. FIRE FIGHTING MEASURES			
Flash point:		Non-flammable	
Autoignition te	mperature:	Non-flammable	
Inflammability	limits:	None	
Explosion risk:		None by itself, but heat produced by reaction with strong acids can generate steam and pressure	
Hazardous con	ubustion products:	Decomposes to produce calcium oxide (CaO), which can react with water to produce steam and pressure	
Extinguishing	media:	Use dry chemical fire extinguisher. Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of burnt limestone. Use appropriate extinguishing media for surrounding fire conditions.	
Fire fighting in	structions:	Keep personnel away from and upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (self-contained breathing apparatus).	
6. ACCIDENT	PREVENTION MEAS	URES	
Individual and	collective precautions:	Avoid creating conditions which release dust – use mechanical ventilation to control dust levels below PEL.	
Avoid inhalation of dust:		Wear NIOSH N-95 particulate respirator if airborne concentration exceeds PEL.	
Cleaning methods for spills:		Use personal protective equipment (see Section 8). Dry methods may be used (vacuuming, sweeping) to collect spilled materials but avoid generating excessive dust. For large spills, evacuate area downwind of clean-up operations to minimize dust exposure. For small spills, store spilled materials in dry, sealed plastic or metal containers. Dust residue on surfaces may be washed with water or vinegar.	
Precautions for the environment	r the protection of nt:	May not be released into surface waters without controls. Prevent release to sewers or waterways.	
Waste Disposal:		Dispose according to federal, provincial/state and local environmental regulations.	
7. HANDLING AND STORAGE			
Handling:	<b>Handling:</b> In open air or in ventilated places, avoid skin and eye contact, avoid creating airborne dust. Kee in tightly closed containers and protect containers from physical damage. An eye wash statio should be readily available where this product is handled.		
Storage:	Store in dry places sheltered from humidity. Keep away from acids and incompatible substances Keep out of reach of children		

# $HIGH \ CALCIUM \ LIMESTONE \ ({\tt continued})$

# 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits: Calcium Carbonate:	OSHA PEL: 15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (respirable) ACGIH TLV: 1 mg/m <sup>3</sup> Ont. Reg. 833 TWAEV: 10 mg/m <sup>3</sup>	
Magnesium Carbonate	OSHA PEL: 15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (respirable) ACGIH TLV: 10 mg/m <sup>3</sup> Ont. Reg. 833 TWAEV: 10 mg/m3	
Silica:	OSHA PEL: $30 \text{ mg/m}^3 / (\% \text{ SiO}_2 + 2) \text{ (total)}$ $10 \text{ mg/m}^3 / (\% \text{ SiO}_2 + 2) \text{ (respirable)}$ ACGIH TLV: 0.025 mg/m <sup>3</sup> (respirable) Ont. Reg. 845 TWAEV: 0.1 mg/m <sup>3</sup>	
Engineering Controls:	Use ventilation and dust collection to control exposure to below applicable limits.	
<b>Respiratory Protection:</b>	Wear NIOSH N-95 particulate respirator if airborne concentration exceeds PEL.	
Eye Protection:	Wear eye protection (goggles, safety glasses and/or face shield). Contact lenses should not be worn.	
Hand Protection:	Wear clean dry gloves	
Skin Protection:	Cover body with suitable clothes (i.e. long sleeve shirt and trousers).	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Odor & Appearance:	Odorless, white or gray powder or stone
pH:	9.4 in saturated water solution at 25°C
Melting point:	950 °C
Boiling point:	2850 °C
Vapor pressure:	Non volatile
Vapor density:	Non volatile
Density:	2.6 - 2.8 g/cc
Solubility:	Slightly soluble in water: 0.013 g/L at 18°C
	Soluble in acids, glycerin and sugar solutions
Specific Gravity:	2.7

# HIGH CALCIUM LIMESTONE (continued)

10. STABILITY AND REACTIVITY		
Stability:		Stable products, not very soluble.
Decomposition temperature:		950°C, forms calcium oxide (CaO) and carbon dioxide(CO <sub>2</sub> )
Reactivity:		Reacts with acids to form calcium salts while generating heat.
		Vicinity of incompatible materials
Conditions to avoid: Incompatible materials:		Acids; reactive fluoridated, brominated or phosphorous compounds; aluminum (may form hydrogen gas), ammonium salts, mercury, hydrogen, magnesium, reactive powdered metals; organic acid anhydrides; nitro-organic compounds; interhalogenated compounds
Hazardous decompos	ition products:	Calcium oxide (CaO)
<b>11. TOXICOLOGICA</b>	AL INFORMATION	
Toxicity:	This product is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product may contain trace amounts of crystalline silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled in the form of quartz or cristobalite. No reported Carcinogenicity, Reproductive Effects, Teratogenicity or Mutagenicity.	
Exposure Limits:	Refer to Section 8.	
Irritancy:	Can cause irritation of eyes, skin, respiratory tract and gastrointestinal tract.	
Chronic Exposure:	Inhalation of silica can cause a chronic lung disorder, silicosis.	

**12. ECOLOGICAL INFORMATION** 

Alkaline substance that increases pH to a maximum of 9.4 in a saturated water solution at 25°C Calcium carbonate is ecologically neutral Uncontrolled spillage in surface waters should be avoided since the increase pH could be detrimental to fish Harmful to aquatic life in high concentration

This material shows no bioaccumulation effect or food chain concentration toxicity.

### **13. DISPOSAL CONSIDERATIONS**

Dispose according to federal, provincial/state and local environmental regulations. If this product, as supplied, and unmixed, becomes a waste, it will not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act.

Product N	lame:
-----------	-------

14. TRANSPOR	TATION IN	FORMATION	
Classification:	TDG HMR US DOT	Not Regulated Not Regulated Not Regulated	
15. REGULATO	ORY INFORM	MATION	
WHMIS		D2A, Materials Causing other toxic affects.	
NFPA		Health $-1$ Fire $-0$ Reactivity $-0$	
HMIS		Health $-1$ Fire $-0$ Reactivity $-0$ Personal Protection - E	
<b>Risk Phrases:</b>		Risk of serious damage to the eyes Keep out of reach of children	
Safety Phrases:		Keep storage container away from humidity Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with water for at least 15 minutes	
CPR (Canada):		This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) of Canada and this MSDS contains all information required by the CPR.	
		Refer to Ontario Regulation 845: Designated Substance – Silica.	
United States EPA		RCRA Hazardous Waste Number: not listed (40 CFR 261.33) RCRA Hazardous Waste Classification (40 CFR 261): not classified CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311(b)(4); CWA, Sec. 307(a), CAA, Sec. 112 CERCLA Reportable Quantity (RQ): not listed. SARA 311/312 Codes: not listed.	
		SARA Toxic Chemical (40 CFR 372.65): not listed. SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ): not listed. All chemical ingredients are listed on the U.S. TSCA Inventory List.	
OSHA	SHA Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A) Specifically Regulated Substance (29CFR 1910): not listed.		
MSHA		Not listed.	

## **16. MISCELLANEOUS OTHER INFORMATION**

An electronic version of this MSDS is available at www.carmeusena.com

The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.