

MATERIAL SAFETY DATA SHEET

Prepared According to 29 CFR 1910, 1200

N/A (Not Applicable) N/E (Not Established)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: Slick
GENERIC NAME: Tire Mounting Lubricant
CHEMICAL FAMILY: Liquid Mixture
PROPER SHIPPING NAME: Not regulated

HIMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HEALTH _____ 1
FLAMMABILITY _____ 0
REACTIVITY _____ 0
PERSONAL PROTECTION _____ B

HAZARD RATING

4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 = INSIGNIFICANT

SECTION II - HAZARDOUS INGREDIENTS IDENTIFICATION INFORMATION

HAZARDOUS COMPONENTS	CAS#	TLV	% WT (OPT)
Sodium metasilicate	6834-92-0	1mg/m ³	<5%

SECTION III - PHYSICAL DATA

PHYSICAL DESCRIPTION: Purple, Viscous Liquid, unscented
BOILING RANGE (°F): 190-210°F
VAPOR PRESSURE: N/E
% VOLATILE: N/A
SOLUBILITY IN WATER: 100
SPECIFIC GRAVITY: 1.00
EVAPORATION RATE: NE
pH:

SECTION IV - SPECIAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: None generally required
PROTECTIVE GLOVES: Impervious
EYE PROTECTION: Safety goggles or glasses
VENTILATION: Room ventilation is generally adequate
OTHER PROTECTIVE EQUIPMENT: Sufficient to prevent skin contact.

SECTION VI - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): Non flammable
UPPER EXPLOSIVE LIMIT: N/E **LOWER EXPLOSIVE LIMIT:** N/E
EXTINGUISHING MEDIA: Use appropriate extinguishing media for the surrounding fire.
SPECIAL FIRE FIGHTING PROCEDURES: Self contained breathing apparatus and full protective clothing should be worn when fighting fires involving chemicals.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY (Materials to Avoid): Strong acids and oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: None known

HAZARDOUS POLYMERIZATION:
Will not occur

SECTION VII - FIRST AID

EYES: Flush with water for at least 15 minutes, be sure to keep eyelids opened. Get immediate medical attention if irritation persists.

SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation persists.

INGESTION: Give milk or water to dilute. INDUCE VOMITING. Get immediate medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION: Remove victim to fresh air. If person is having difficulty in breathing, perform artificial respiration and get immediate medical attention.

SECTION VIII - HEALTH HAZARDS

EFFECTS OF OVEREXPOSURE (Primary Route of Entry)

SKIN: Possible irritant
EYES: Possible irritant
INHALATION: None

Ingestion: None suspected
CARCINOGENS:

NTP: **OSHA:** **IARC:** **ACGIH:**
OTHER:

SECTION IX - STORAGE AND HANDLING

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
Use common sense and sound industrial hygiene practices when handling this material as well as any other materials. Keep container closed when not in use. Wash hands after handling. Keep out of reach of children. Wear appropriate personal protection to avoid eye and skin contact.

SECTION X - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear necessary personal protective equipment. Dike area to prevent spreading of the spilled material. Cover with an inert absorbent (sand, clay, etc.), shovel into appropriate containers, and dispose of in accordance with federal, state, and local regulations.

EMPTY CONTAINERS DISPOSAL: Any disposal practices must be in compliance with federal, state and local laws. Any questions regarding disposal should be directed to the proper government agency.

Manufactured By: WARSAW CHEMICAL CO., INC.
390 ARGONNE ROAD, P.O. BOX 858
WARSAW, IN 46581
574-267-3251 FAX 574-267-3884